



THE BOWLER'S COMPANY™



MAINFRAME™

## Physical Properties

	<u>Mainframe</u>
Color:	Multi-Color Mainframe Imagery
Coverstock:	Ultra Clear™ Polyester
Weight Block:	Traditional 3-piece Core
Ball Finish:	3500-grit Polish
Logos:	Eye of the Storm CG,
Durometer:	80-83
Flare Potential:	0" - 1" (Low)
Radius of Gyration:	2.69
Differential:	.006
Available Weights:	12-16 lbs.



### Resurfacing Method:

Follow the steps below to take the ball back to "out of the box" condition. Items needed; Abralon pads in grits of 500, 1000, 2000 and 4000, Xtra Shine™ polish, a ball spinner and water. All sanding should be done on four sides of the ball. Side one- center of grip up, flip the ball 180 degrees for side two, turn 90 degrees for side three and flip another 180 degrees for side four.

1. Using the 500-grit Abralon pad, sand the ball for 15 seconds on each side, switch to the 1000-grit pad for 20 seconds on each side. Moving to the 2000-grit pad sand for 25 seconds on each side.
2. Using the 4000-grit Abralon pad, sand the ball for 30 seconds on each side.
3. Use the Xtra Shine on 4 sides of the ball for 30 seconds on each side.

### Suggested Maintenance:

Storm suggests using Xtra Clean™ all purpose bowling ball cleaner to clean your bowling ball after every bowling session.

To touch up the surface, skip step #1 and use steps #2 and #3 only. Storm suggests using steps #2 and #3 from above, every 20-30 games. Use all steps every 50-60 games. This will increase longevity and create a more consistent reaction for your new Storm bowling ball.